

LOW VOLTAGE DC POWERED TELECOMMUNICATIONS CUSTOMER
SERVICE TERMINAL HAVING TELEPHONE WIRE INTERCONNECTION
AND A HOT-SWAPPABLE LOW VOLTAGE BATTERY MODULE

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This non-provisional patent application claims the benefit of co-
pending provisional patent application Serial No. 60/209,277 filed June 2,
2000 and entitled INTEGRATED TELECOMMUNICATIONS ACCESS
DEVICE USING SDSL, incorporated herein by reference.

10 This non-provisional patent application claims the benefit of co-
pending provisional patent application Serial No. 60/279,910 filed March 29,
2001 and entitled TELECOMMUNICATIONS CUSTOMER SERVICE
TERMINAL, incorporated herein by reference.

Design patent application Serial No. 29/138,897 filed March 21, 2001
and entitled BACKUP POWER PACK.

15 Design patent application Serial No. 29/138,901 filed March 21, 2001
and entitled TELECOMMUNICATIONS CUSTOMER SERVICE
TERMINAL.

20 ~~Non-provisional patent application Serial No. xx/xxx,xxx filed May --,
2001 and entitled LOW VOLTAGE DC POWERED
TELECOMMUNICATIONS CUSTOMER SERVICE TERMINAL HAVING
OPTIONAL HOT-SWAPPABLE LOW VOLTAGE BATTERY MODULE.
(Attorney Docket No. 40405.830015.000)~~

BACKGROUND OF THE INVENTION

Field of the Invention:

25 This invention relates to the field of telecommunications, and more
specifically to a telecommunications Customer Service Terminal (CST) that is

09872084-053101
553
21

operable to deliver carrier-class analog voice and digital data to a telephone user such as a home or a small business.

Description of the Related Art:

5 The use of telecommunications customer service terminals, also known as Integrated Access Devices or IADs, is known. However, there is a need in the art for a small, simple, inexpensive and conveniently-wireable CST that provides both analog voice and digital data to a relatively small-need telecommunications users.

SUMMARY OF THE INVENTION

10 This invention provides a telecommunications CST wherein all of the input and output wiring comprises telephone wire that is readily available to personnel that install the CST. Relative to this feature of the invention, most telephone installation trucks carry quantities of relatively inexpensive 24, 26 and 28 gage telephone wire. This invention provides that readily available
15 telephone wire of this type is used to connect the CST to its low voltage DC input power, to an input telecommunications line, and to the various telephones and data terminals that are serviced by analog/digital outputs of the CST.

20 This invention provides a small, simple and inexpensive single line entry telecommunications CST that is powered by low voltage Direct Current (DC) in the absence of an on/off switch. That is, so long as the CST is provided with a low voltage DC input, the CST remains operative or remains in an on state.

25 A low-voltage DC power supply may be used that includes a manually-removable and "hot swappable" low voltage battery pack that operates to bridge failure of a primary high voltage alternating current (AC) power input to the low voltage power supply.

09872084, 053101

Low-voltage DC power is supplied to the CST in the absence of an on/off switch by selecting for use either (1) a first power supply whose input is a high voltage AC (for example, 110 VAC) and whose output is a low voltage DC (for example, 24 VDC), or (2) a second power supply module
5 whose input is a high voltage AC (for example, 110 VAC), whose output is a low voltage DC (for example, 24 VDC), and which includes a manually-removable DC battery pack that operates to supply a low voltage DC output should the high voltage AC input to this second type of power supply fail.

Since the CST does not have an on/off switch, only the present of a
10 low voltage DC input is required to render the CST operative. Should the above-mentioned AC power failure for this second type of power supply extend for a relatively long time interval, for example eight hours, the currently in use DC battery pack may have to be replaced with a freshly charged DC battery pack. In this event, the CST experiences only a short
15 period of inoperativeness while the old battery pack is manually removed and a freshly charged battery pack is manually inserted.

This second type of power supply module includes circuitry that is operable to monitor the state of charge of the manually removable DC battery pack, as well as circuitry that responds to the presence or absence of a high
20 voltage AC input.

Indicators such as Light Emitting Diodes (LEDs) are provided to indicate the state of charge of the DC battery pack and to indicate the active/inactive state of the high voltage AC power.

This second type of power supply is constructed and arranged such
25 that, so long as high voltage AC input power is applied thereto, manual removal and replacement of the DC battery pack can be affected without disturbing the supplying of low voltage DC power to the CST, i.e. the battery pack can be "hot swapped" while the CST continuously remains operative.

09872084-053101
TOTAL 4822860

5

10

15

20

25

03034-0370

Mbps (U. S. and Canada) or 2.048 Mbps (Europe) in each direction on a duplex line that is symmetric because the data rate is the same in both directions.

DSL is a technology for bringing high bandwidth information to homes and small businesses over ordinary copper telephone lines, wherein xDSL refers to different variations of DSL, such as, but not limited to, ADSL, CDSL, HDSL, IDSL, RADSL, SDLS, UDSL and VDSL. A DSL can carry both data and voice signals wherein the data part of the line is continuously connected.

Assuming that the home or small business is close enough to a telephone company central office that offers DSL, the home or small business may be able to receive data at rates up to 6.1 megabits per second, thus enabling continuous transmission of motion picture video, audio, and even 3-dimensional effects.

While telecommunications system 10 will be described as having a SDSL input 11, its spirit and scope includes virtually any type of DSL 11.

Grounded low-voltage DC input power (i.e., 24 VDC) is applied to CST 12 by way of a telephone wire 15. As shown by dotted line 16, 24 VDC power 15 is optionally supplied by a first wall-mounted power supply 20 or by a second wall-mounted power supply 21, by way of the respective telephone wires 23 or 26.

Power supply 20 is of a well known type that receives a high-voltage input, such as 110 VAC input 22, and operates to supply a low-voltage DC output, such as 24 VDC, on telephone wire 23.

Power supply 21 includes a first component 24 that operates similar to power supply 20. That is, as long as 110 VAC input 25 to power supply 24 remains active, 24 VDC telephone wire output 26 of component 24 remains

09872084 053101

active. In addition, power supply 21 includes a manually-replaceable 24 VDC battery pack 27 that constitutes a hot swappable backup power supply for component 24 and AC input 25.

5 Circuitry within component 24 (not shown) operates to activate a battery-state indicator 30 in accordance with the state of charge of 24 VDC battery pack 27.

10 Power supply 21 is constructed and arranged so that when indicator 30 indicates the need to manually remove a 24 VDC battery pack 27 that is currently resident on base member 32, that particular battery pack 27 can be removed and replaced with a fully charged battery pack 27. So long as 110 VAC input 25 to power supply 21 remains active, this removal and replacement of a battery pack 27 does not interrupt operation of CST 12.

15 In this construction and arrangement of telecommunications system 10, all wiring, with the exception of 110 VAC inputs 22 and 25, is American Wire Gage (AWG) telephone wiring, such as 24, 26, or 28 gage telephone wire that is readily available to telecommunications workers who are building or connecting system 10.

20 CST 12 and power supply 20 or power supply 21 may be mounted in relatively close proximity to each other, for example on a vertically extending wall 33. Optionally the housing of CST 12 may be a weather-proof housing that is constructed and arranged for mounting out of doors.

25 Since CST 12 does not have an on/off switch, only the present of low voltage DC input 15 is required to render CST 12 operative. Should AC power 25 fail for an extend period of time, for example for eight hours, indicator 30 may indicate that a currently in use DC battery pack 27 should be

09872034-053101
FOI 50-4802/860

replaced by a freshly charged DC battery pack 27, whereupon CST 12 experiences only a short period of inoperativeness as the old battery is removed and a fresh battery is inserted in power supply 21.

What is claimed is: